


Zone of Confidence (ZOC) Diagram



ZOC CATEGORIES

| ZOC | COLOR | POSITION<br>ACCURACY   | DEPTH<br>ACCURACY                                  | SEAFLOOR<br>COVERAGE   |
|-----|-------|--|--|--|
| A1  |       | ± 5 m + 5% depth<br>± 16.4 ft + 5% depth                                 | = 0.50 m +1% d<br>= 1.6 ft +1% d<br>= 0.3 fm +1% d | All significant seafloor features detected.  |
| A2  |       | ± 20 m<br>± 65.6 ft  | = 1.00 m +2% d<br>= 3.3 ft +2% d<br>= 0.6 fm +2% d | All significant seafloor features detected.  |
| B   |       | ± 50 m<br>± 164.0 ft   | = 1.00 m +2% d<br>= 3.3 ft +2% d<br>= 0.6 fm +2% d | Uncharted features hazardous to surface navigation are not expected but may exist. |
| C   |       | ± 500 m<br>± 1640.4 ft   | = 2.00 m +2% d<br>= 6.6 ft +2% d<br>= 1.1 fm +2% d | Depth anomalies may be expected.   |
| D   |       | Worse than ZOC C   | Worse than ZOC C                                   | Large depth anomalies may be expected.   |
| U   |       | Unassessed - The quality of the bathymetric data has yet to be assessed. |  |  |

# 165960G

## NOAA CUSTOM CHART NOTES GEOSPATIAL DATABASE VERSION 3.0B - 20 FEBRUARY 2025

The records of the NOAA Custom Chart Notes Geospatial Database are current as of February 20, 2025. Subsequent additions and refinements are to be expected. Please refer to all available navigational publications for complete information about the charted area.

### CAUTION CHART UPDATES

This NOAA Custom Chart contains up-to-date information only as of the time of creation, and will become outdated. Mariners are advised to visit <https://distribution.charts.noaa.gov/navigation-updates/> to check for critical and routine updates, and to render a new NOAA Custom Chart when the ENC data used to make the chart is updated. Notices to Mariners are not issued for corrections to this NOAA Custom Chart.

### AUTHORITIES

Hydrography and topography by the National Ocean Service, Coast Survey, with additional data from the Corps of Engineers, Geological Survey, U.S. Coast Guard and National Geospatial-Intelligence Agency.

### COMMENTS REQUESTED

NOAA encourages users to submit inquiries, discrepancies, or comments about this chart via NOAA's ASSIST tool at <https://nauticalcharts.noaa.gov/customer-service/assist/>.

### CAUTION AUTOMATED CHART GENERATION

This NOAA Custom Chart has been automatically rendered from NOAA Electronic Navigational Chart (NOAA ENC®) data. Mariners using this NOAA Custom Chart are advised that this is a static reproduction of the NOAA ENC®. This NOAA Custom Chart has not been individually quality checked or adjusted for optimal use for navigation. The portrayal may be at a different scale from that of the original NOAA ENC®. Mariners are advised to use caution when using this NOAA Custom Chart for navigation and are encouraged to use the latest NOAA ENC® to access the most up-to-date information. Mariners must also comply with all applicable regulatory requirements.

### HEIGHTS

Heights of fixed aids to navigation and vertical clearances of overhead obstructions will be shown in feet if the units are set to feet or fathoms. If units are set to meters, heights will be shown in meters. Land elevation values are shown in meters only.

### WATER LEVELS, CURRENTS, AND TIDES

Real-time water levels, tide predictions, and tidal current predictions are available on the internet from NOAA's Center for Operational Oceanographic Products and Services (CO-OPS) at [https://tidesandcurrents.noaa.gov/water\\_level\\_info.html](https://tidesandcurrents.noaa.gov/water_level_info.html) and [https://tidesandcurrents.noaa.gov/currents\\_info.html](https://tidesandcurrents.noaa.gov/currents_info.html).

### ABBREVIATIONS

For complete list of Symbols and Abbreviations, see Chart No. 1.

# 165960G

## POLLUTION REPORTS

Report all spills of oil and hazardous substances to the National Response Center via 1-800-424-8802 (toll free), or to the nearest U.S. Coast Guard facility if telephone communication is impossible (33 CFR 153).

## WARNING

The prudent mariner will not rely solely on any single aid to navigation, particularly on floating aids. See U.S. Coast Guard Light List and U.S. Coast Pilot for details.

## SUPPLEMENTAL INFORMATION

Consult U.S. Coast Pilot 9 for important supplemental information.

Refer to charted regulation section numbers.

## VERTICAL DATUM

Overhead clearances are referred to Mean High Water (MHW).

## COLREGS, 80.1705 (SEE NOTE A)

International Regulations for Preventing Collisions at Sea, 1972. The entire area of this chart falls seaward of the COLREGS Demarcation Line.

## CAUTION

Temporary changes or defects in aids to navigation are not indicated on this chart. See Local Notice to Mariners.

## AIDS TO NAVIGATION

Consult U.S. Coast Guard Light List for supplemental information concerning aids to navigation.

## RADAR REFLECTORS

Radar reflectors have been placed on many floating aids to navigation. Individual radar reflector identification on these aids has been omitted from this chart.

## ADDITIONAL INFORMATION

Additional information can be obtained at [www.nauticalcharts.noaa.gov](http://www.nauticalcharts.noaa.gov)

## SOUNDING DATUM

Soundings referred to Mean Lower Low Water (MLLW).

## NOTE A

Navigation regulations are published in Chapter 2, U.S. Coast Pilot 9. Additions or revisions to Chapter 2 are published in the Notices to Mariners. Information concerning the regulations may be obtained at the Office of the Commander, 17th Coast Guard District in Juneau, AK or at the Office of the District Engineer, Corps of Engineers in Anchorage, AK.

Refer to charted regulation section numbers.

## 165960G

### CAUTION LIMITATIONS ON THE USE OF RADIO SIGNALS

Limitations on the use of radio signals as aids to marine navigation can be found in the U.S. Coast Guard Light Lists and National Geospatial-Intelligence Agency Publication 117.

Radio direction-finder bearings to commercial broadcasting stations are subject to error and should be used with caution.

### CAUTION UNEXPLODED ORDNANCE

Mariners are cautioned against anchoring, dredging or trawling in this area due to the possible existence of unexploded ordnance in the vicinity of Chiniak Bay and Marmot Bay. Reported 2013

### CAUTION ALERT AREA

Vessels entering or departing Kodiak/St. Paul Harbor with an air draft of 42 meters/138 feet or higher require operating changes for aircraft at the Kodiak airport and should notify the Federal Aviation Administration's (FAA) Anchorage Air Route Traffic Control Center at (907) 269-1915 (primary) or (907) 269-1103 (secondary) of their presence. Additional information is available in Coast Pilot 9.

### LOCAL MAGNETIC DISTURBANCE

Differences of as much as 20° to 40° from the normal variation have been observed at 57°43'51"N, 152°30'50"W.

### CAUTION SUBMERGED CABLES AND PIPELINES

Additional uncharted submarine pipelines and submarine cables may exist within the area of this chart. Not all submarine pipelines and submarine cables are required to be buried, and those that were originally buried may have become exposed. Mariners should use extreme caution when operating vessels in depths of water comparable to their draft in areas where pipelines and cables may exist, and when anchoring, dragging or trawling.

Covered wells may be marked by lighted or unlighted buoys.

### CAUTION WOMENS BAY

The anchorage berths are for emergency use only and shall not be used for protracted anchorage without specific authority.

### CAUTION

Improved channels are subject to shoaling, particularly at the edges.

### CAUTION WOMENS BAY

Depths outside of recent survey coverage reflect conditions prior to the earthquake of 1964.

### NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio station listed below provides continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations. Kodiak, AK WXJ-78 162.550 MHz

## 165960G

### NOAA WEATHER RADIO BROADCASTS

The NOAA Weather Radio station listed below provides continuous weather broadcasts. The reception range is typically 20 to 40 nautical miles from the antenna site, but can be as much as 100 nautical miles for stations at high elevations.  
Pillar Mtn., AK WNG-531 162.525 MHz